**ADVANCED WATERLESS PRIMO TECHNOLOGY VS. OBSOLETE WATER-JACKET DESIGN**



304 SS INTERIOR · 1" DRAIN VALVE

INDUSTRIAL WAX MELTER & HEATED TANK

# PRIMO 1000

A digitally controlled, waterless melting system engineered for continuous daily production. Built to deliver fast, even, repeatable heat for integrated filling lines, larger production runs, and bulk batch heating. Not hobby use.

- 2–3× Faster Melting
- Up to 50% Lower Energy Cost
- Waterless · No Water Jacket
- Built for Continuous Production
- Stainless Steel Lid Included

Product page →

| CAPACITY | TEMP RANGE | POWER | INTERIOR | SPRING 2026 BASE PRICE |
|---|---|---|---|---|
| 1226 lb / 158 gal (556 kg / 598 L) | 32–212°F (0–100°C) | 2,000 W | 304 SS | $7,995 |

## TECHNICAL SPECIFICATIONS

### PERFORMANCE & CAPACITY

| | |
|---|---|
| Working Capacity | 1226 lb (556 kg) / 158 gal (598 L) |
| Operating Temperature | 32–212°F (0–100°C) |
| X-Treme Option | Up to 400°F (204°C) |
| Heat-Up Rate | 2–3× vs. water-jacket |
| Energy Use | Up to 50% lower |

### HEATING & CONTROLS

| | |
|---|---|
| Heating Type | PRIMO Waterless Heating System |
| Heating Power | 2,000 W |
| Electrical Service | 110–120 V, 220–240 V, 480 V or 600 V |
| Controller | Digital material-temperature |

### CONSTRUCTION & MATERIALS

| | |
|---|---|
| Inner Tank | 304 stainless, #4 finish |
| Outer Shell | Impact-resistant steel |
| Insulation | Energy Star qualified |
| Interior | Rounded, easy-clean |
| Material Integrity | US steel, Hg/Pb/rad-free |

### DISPENSING & SAFETY

| | |
|---|---|
| Drain Valve | Standard 1" 304 SS |
| Ball Valve | 1" brass or 304 SS |
| Dispensing | Heated spout, clog-free |
| Power Switch | Illuminated, resettable |
| Protection | Reset breaker / fuses |

### DIMENSIONS




| INNER DIMENSIONS | |
|---|---|
| Inside Diameter | 36.0" |
| Inside Depth | 36.0" |

| OUTER DIMENSIONS | |
|---|---|
| Length × Width | 38.0" × 38.0" |
| Height | 38.0" |

## ENGINEERED ADVANTAGES



**WATERLESS HEATING**
No water jacket to maintain, refill, or replace. Less downtime and no corrosion.

**EVEN HEAT DISTRIBUTION**
Controlled, uniform heating delivers consistent, repeatable production batches.

**DIGITAL TEMP CONTROL**
Digital material-temperature control holds target temperature for repeatable processing.

**RUGGED INSULATED BUILD**
304 stainless tank inside an impact-resistant insulated shell, built for long industrial service life.

## APPLICATIONS

- Candle & Wax
- Cosmetics & Personal Care
- Food
- Adhesives & Hot Melt
- Industrial Materials
- Beekeeping & Apiary

## OPTIONS & ACCESSORIES

| | |
|---|---|
| Smooth-weld food-grade interior | +$1,600 |
| Hinged lid + agitator/mixer | +$1,875 |
| 24" SS welded stand | +$725 |
| SNAP melting-tank wax filter | +$69.95 |
| Custom configurations & sizing | on request |

Spring 2026 pricing, subject to change.
Current pricing at WaxMelters.com

## WHAT'S INCLUDED

- 304 stainless double-walled insulated tank
- Stainless steel lid
- Standard 1" 304 SS drain valve + 1" brass or SS ball valve
- Factory-set digital temperature controller
- Professionally palletized for safe transit